

135H-150H Series

Heavy Wall Storefront Doors



Kansas State University
Bramlage Coliseum
Manhattan, KS

Ideal for high traffic areas, the 2" thick with 3/16" wall thickness heavy wall doors are designed to withstand greater daily impact. Manko's heavy wall entrance door options come in two stile widths; 3-1/2" medium stile (**135H series**), and 5" wide stile (**150H series**). Both doors come standard with 10" bottom rail, however additional sizes are available.

All of Manko's doors are fabricated utilizing a telescoping mortise and tenon joint coupled with a horizontal shear block, and then further reinforced with a 3/8" steel tie rod and sleeve ensuring long lasting durability and structural integrity. Each set of Manko's pairs of doors come standard with double adjustable astragals and poly-pile weathering.

Multiple hardware options are available, however hardware compatibility with a specific door series must be taken into consideration, whether that be manufacturer's standard hardware or custom hardware.



135H & 150H Product Features

Medium (3 1/2") and Wide Stile (5") Profiles

2" Door Thickness

3/16" Wall Thickness

3-Way Corner Construction

Range of Mid-Rail Options

ADA Compliant - 10" Bottom Rail

3/16" - 1" Glazing Infill

Standard & Custom Hardware Options Available

Anodized and AAMA 2605 Paint Finishes

Doors at a Glance

Series	Stile	Door Thickness	Wall Thickness	High Traffic Performance	Thermal Performance
100	Narrow	1 3/4"	1/8"	●	
135	Medium	1 3/4"	1/8"	●	
150	Wide	1 3/4"	1/8"	●	
135H	Medium	2"	3/16"	●●	
150H	Wide	2"	3/16"	●●	
135i	Medium	2 1/8"	1/8"	●	●
150i	Wide	2 1/8"	1/8"	●	●
150xpt	Wide	2 9/16"	1/8"-3/16"	●	●

Kansas State University
Morgan Family Arena
Manhattan, KS



Visit www.mankowindowsystems.com
Or scan the QR code for more information on
Manko's Heavy Wall Storefront Door Series

