

2135xpt Series

Structural & Thermal Performances



2135xpt SERIES – AAMA PERFORMANCE RESULTS

	AAMA Performance Rating	Air Infiltration @ 6.24 psf	Water (psf)	Design Pressure	Structural Overload Pressure
Fixed	AW-PG100-F	≤ .1 cfm/ft2	12.0 psf	100 psf	150 psf
Single Hung	AW-PG50-HS	≤ .3 cfm/ft2	10.0 psf	50 psf	75 psf

WHOLE WINDOW U-VALUE (BTU/HxFT²)

Center of Glass U-Value	Whole Window U-Value per NFRC 100*	
	Fixed	Slider
0.41	0.45	0.47
0.38	0.42	0.45
0.35	0.40	0.43
0.32	0.37	0.41
0.29	0.35	0.38
0.26	0.32	0.36
0.23	0.30	0.34
0.20	0.27	0.32

All values shown are calculated with Manko standard warm edge insulated glass units

WHOLE WINDOW SOLAR HEAT GAIN COEFFICIENT

Center of Glass SHGC	Whole Window SHGC per NFRC 200*	
	Fixed	Slider
0.50	0.40	0.46
0.45	0.36	0.42
0.40	0.32	0.37
0.35	0.28	0.33
0.30	0.24	0.28
0.25	0.21	0.24
0.20	0.17	0.19
0.15	0.13	0.15

All values shown are calculated with Manko standard warm edge insulated glass units

WHOLE WINDOW VISIBLE LIGHT TRANSMITTANCE

Center of Glass VLT	Whole Window VLT per NFRC 200 ¹	
	Fixed	Slider
0.80	0.60	0.70
0.70	0.52	0.61
0.60	0.45	0.53
0.50	0.37	0.44
0.40	0.30	0.35
0.30	0.23	0.26
0.20	0.15	0.13
0.10	0.07	0.09

All values shown are calculated with Manko standard warm edge insulated glass units

*U-Values and SHGC have been calculated using Manko standard insulated glass unit construction with Tri-Seal airspace and standard sealants. Substitution of different airspace and/or sealants will effect values. All values listed have been calculated using standard NFRC 100 and NFRC 200 procedures. Some values listed have been extrapolated for clarity and ease of presentation. All values listed have been calculated at standard NFRC Gateway Sizes.

2135xpt Series

Hardware Options and Sizing Capabilities

2135xpt SERIES STANDARD & OPTIONAL HARDWARE

	Tandem Stainless Steel Rollers	Field Adjustable Rollers	Stainless Steel Roller Track Cap	Integral Continuous Pull Handle	Head Mounted Limit Stops	Single Cam Action Sweep Lock	Single Cam Action Sweep Lock	Dual Cam Action Sweep Lock
XO / OX	S	S	O	S	O	S	O	O
XOX	S	S	O	S	O	S	O	O

S = Standard Hardware O = Optional Hardware

*Sash Weight Limitations Apply. **Standard on Sash Weight exceeding 45 lbs

SIZING CAPABILITIES FOR 2135xpt WINDOW (Frame Size)

Configuration (with hardware)	Width		Height		Maximum Sq Ft.
	Minimum	Maximum	Minimum	Maximum	
Fixed	12"	84"	12"	80"	≤38
XO / OX	30"	98"	20"	78"	≤30
XOX	36"	98"	20"	78"	≤40

GLAZING INFILL OPTIONS

	1"	1 1/8"
Glazing	S	**O
S = Standard Infill O = Optional		
**Hermetically sealed blind units are available		