

# 7035 & 7041 Series

## Hung Windows



New Hampshire St. Lofts  
Lawrence, KS

The **7035** and **7041** series hung windows were designed to maintain the economy of systems much lighter in duty, while being a heavy-duty window option. The **7035** series has an overall frame depth of 3 1/2" and comes standard as a true single hung or fixed configuration, while the **7041** series, with a 4 1/2" frame depth, has the option of being double hung along with the single hung or fixed configuration. Using the traditional two-part pour and debridged thermal break, these windows do offer some thermal efficiency. They come standard with 1" glazing infill, and have the luxury of having tilt-in sashes making maintenance easier and more accessible from the interior side.



**7035** (3 1/2" Frame Depth )



**7041** (4 1/2" Frame Depth )

### Product Features

- Fixed, Single, or Double Hung (DH—7041 only)
- AW Hung Window System
- Pour & Debridged Thermal Break
- Standard 1" Glazing Infill
- Vertical & Horizontal Stacking Options
- Standard Class 5 Balances
- Tilt-In Operable Sash
- Panning & Receptors Systems Available
- NFRC 100, 200 & 500 Certified
- Class 1 Anodized Finishes
- AAMA 2605 Paint Finishes

### 7035 AAMA Performance Values

Type	Performance Rating	Air Infiltration (ASTM E283)	Water Resistance (ASTM E547 & E331)
Fixed	AW-PG100	≤ 0.1 cfm/ft <sup>2</sup>	12 PSF
Hung	AW-PG50	≤ 0.3 cfm/ft <sup>2</sup>	10 PSF

### 7041 AAMA Performance Values

Type	Performance Rating	Air Infiltration (ASTM E283)	Water Resistance (ASTM E547 & E331)
Fixed	AW-PG100	≤ 0.1 cfm/ft <sup>2</sup>	12 PSF
Hung	AW-PG50	≤ 0.3 cfm/ft <sup>2</sup>	10 PSF

### 7035/7041 NFRC U-Values | Fixed

Glass Types	U-Values Air(Argon)	SHGC	CR
Clear SN 68 #2 / Clear	0.40 (0.36)	0.34	44
Clear SNX 62/27 #2 / Clear	0.40 (0.36)	0.25	44
Clear SB60 #2 / Clear	0.40 (0.36)	0.36	44
Clear SB70 #2 / Clear	0.40 (0.36)	0.25	44
Clear SN 68 #2 / IS 20 #4	0.35 (0.33)	0.33	44

\* Values Calculated with Manko's Warm Edge Spacer

Values Subject to Change without Notice

### 7035/7041 Series NFRC U-Values | Operable

Glass Types	U-Values Air(Argon)	SHGC	CR
Clear SN 68 #2 / Clear	0.49 (0.45)	0.29	35
Clear SNX 62/27 #2 / Clear	0.48 (0.45)	0.21	35
Clear SB60 #2 / Clear	0.49 (0.46)	0.30	35
Clear SB70 #2 / Clear	0.48 (0.45)	0.22	35
Clear SN 68 #2 / IS 20 #4	0.44 (0.42)	0.28	35

\* Values Calculated with Manko's Warm Edge Spacer

Values Subject to Change without Notice

Tacos & Tequila  
Greeley, CO

# TACOS & TE



Visit [www.mankowindowsystems.com](http://www.mankowindowsystems.com)  
 Or scan the QR code for more information on  
 Manko's 7035 & 7041 Series Hung Windows