

# MANKO 2135xpt SERIES 3 1/2" ARCHITECTURAL GRADE Fixed and HORIZONTAL SLIDING (XO, OX) WINDOW SYSTEM THERMAL PERFORMANCE CAPABILITIES

Whole Window U-Value (BTU/HxFT <sup>2</sup> )		
COG U-Value	Whole Window U-Value Per NFRC-100*	
	Fixed	Slider
0.41	0.45	0.47
0.38	0.42	0.45
0.35	0.40	0.43
0.32	0.37	0.41
0.29	0.35	0.38
0.26	0.32	0.36
0.23	0.30	0.34
0.20	0.27	0.32

All values shown are calculated with Manko standard Tri-Seal insulated units

Whole Window Visible Light Transmittance		
COG Vt	Whole Window Vt Per NFRC-200 <sup>1</sup>	
	Fixed	Slider
0.80	0.60	0.70
0.70	0.52	0.61
0.60	0.45	0.53
0.50	0.37	0.44
0.40	0.30	0.35
0.30	0.23	0.26
0.20	0.15	0.13
0.10	0.07	0.09

All values shown are calculated with Manko standard Tri-Seal insulated units

Whole Window Solar Heat Gain Coefficient		
COG SHGC	Whole Window SHGC Per NFRC-200*	
	Fixed	Slider
0.80	0.64	0.73
0.75	0.60	0.69
0.70	0.56	0.64
0.65	0.52	0.60
0.60	0.48	0.55
0.55	0.44	0.51
0.50	0.40	0.46
0.45	0.36	0.42
0.40	0.32	0.37
0.35	0.28	0.33
0.30	0.24	0.28
0.25	0.21	0.24
0.20	0.17	0.19
0.15	0.13	0.15
0.10	0.09	0.10
0.05	0.05	0.06


All values shown are calculated with Manko standard Tri-Seal insulated units

\* U-values and SHGC have been calculated using Manko standard insulated glass unit construction with Tri-Seal airspacers and standard sealants. Substitution of different airspacers and/or sealants will effect values.

All values listed have been calculated using standard NFRC-100 and NFRC-200 procedures. Some values listed have been extrapolated for clarity and ease of presentation.

All values listed have been calculated at standard NFRC Gateway Sizes.

Manko Window  
Systems Inc.  
800 Hayes Drive  
Manhattan, KS.  
66502  
PH: (800) 642 1488  
FX: (800) 576 2656



Manko – Aurora, CO.  
17500 E. 22<sup>nd</sup> Avenue  
Aurora, CO. 80011  
PH: (888) 642 1488  
FAX: (303) 375 0669

Manko– Des Moines, IA.  
3001 McKinley Avenue  
Des Moines, IA. 50321  
PH: (515) 288 7427  
FAX: (515) 288 6968

**MANKO**  
WINDOW SYSTEMS, INC.